


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REV ECR DESCRIPTION

2 17-0106 -5 CH'D DIMS WAS 38.88 IS 38-7/8", WAS 5.0 IS 5" SEWN TYP. ADDED LOAD RATING NOTE.





2

DATE

4/26/2017

INITIAL

APPROVED

JAG

NOTE: STRAP MUST BE LOAD RATED TO MINIMUM 118 LBS.

## DART

SLING, MAIN ROTOR HUB

RBE350A91-3105-02-5


MAIL					S OTHERWISE SPECIFIED
HEAT TREAT				.xxx ± .005	NSIONS ARE IN INCHES FRACTIONS ± 1/8
FINISH				.XX ± .01 .X ± .1	ANGLES ±.5° SURFACES = 125/
SPEC				1. BREAK AL	L SHARP EDGES
DRAWN BY:	SMITH			.015 x 45° OR .015R - 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 1. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
CHECKED:	RJC 04/27/2017				
OPPS APPR:	AA 05/05/2017				
QA APPR:	JL 05/10/2017			USED ON MODEL	
APPROVED:	JAG 05/17/2017			EUROCOPTER AS350	
SCALE	1.1	DATE	9/2	20/2013	SHEET 2 OF 3

(-5)

STRAP ASSEMBLY

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace.

## FIRST ARTICLE WEIGHT TEST



INSPECTING & TESTING PROCEDURES FOR THE RBE350A91-3105-02, SLING, MAIN ROTOR HUB. THIS ASSEMBLY IS DESIGNED EXCLUSIVELY FOR HOISTING AND INSTALLING/REMOVING THE AS350 MAIN ROTOR STARFLEX HUB. THIS ASSEMBLY SHOULD BE INSPECTED BEFORE EACH USE. REPLACE ANY ITEMS THAT ARE DAMAGED OR SUSPECTED OF DAMAGE BEFORE USING!

## FIRST ARTICLE WEIGHT TEST

- 1. AFTER INSPECTION, STRAPS TO BE TESTED INDIVIDUALLY. PLACE STRAP ASSEMBLY ON A OVERHEAD LIFTING DEVICE. ATTACH D-RINGS TO AN APPROPRIATE TEST WEIGHT OF 118 LBS. USE APPROPRIATE DEVICES TO LOCK INTO FIXTURE.
- 2. THE SLING, MAIN ROTOR HUB TO BE TESTED. PLACE SLING ASSEMBLY ON A OVERHEAD LIFTING DEVICE. ATTACH MASTER LINK TO AN APPROPRIATE TEST WEIGHT OF 248 LBS. USE APPROPRIATE DEVICES TO LOCK INTO FIXTURE.
- 3. LIFT WEIGHT FOR AT LEAST 5 MINUTES, CONTINUALLY CHECKING FOR CRACKS, DEFLECTION, OR DISTORTION.
- 4. REMOVE WEIGHT AND RE-INSPECT SLING, CHECKING FOR STRESS CRACKS, BENDING, OR DISTORTIONS. IF DEFORMATION IS VISUALLY DETECTED, THE TOOL MUST BE REJECTED.

nspector:	
TESTER:	
S.N.:	
DATE:	



190 S. Danebo Ave., Eugene, OR. 97402 1-800-556-4166 e-mail: sales@dartaero.com

dartaerospace.com

SLING, MAIN ROTOR HUB

RBE350A91-3105-02

CUSTOMER 1 OF 1

3 OF 3

DATE 9/20/2013 SHEET